



ISC-16UG

Fiber Optic Splice Closure

Features

- ◆ Max for 36 SC simplex adaptors
- ◆ Max for 32 drop cables
- ◆ Can hold 1x32, 1x16, 1x8 etc PLC splitter
- ◆ May be used for cut, uncut and taut sheath applications.
- ◆ May be used for all fiber optic cable.
- ◆ Sheath retention & central strength member fasten system included.
- ◆ Ribbed closure construction and lightweight plastic provides strength and resistance to chemical and U.V attack
- ◆ Installation and reentry with a minimum of tools
- ◆ Mechanical sealing way, re-enterable and reusable
- ◆ All hardware are included
- ◆ Closure can be flash tested
- ◆ RoHS compliance

Application

- ◆ Watertight, Underground, Aerial, Vault and Wall Mountable

Specifications

Mechanical Structure and Dimension

- ◆ Spliced fiber storage capacity(single fusion) : 72F fusion splice adaptors
- ◆ Splice Tray : Tray 204B (max for 24F), max hold 3 trays
- ◆ PLC splitter : 1x32, 1x 16 PLC, 1x8 splitter
- ◆ Cable ports : 1 large round port+ 4 round ports
- ◆ Max. diameter of cable(mm) :
 - 1 large round port: for 1 loop cable with max dia 17mm
 - 4 round ports: each port for 1 cable with max dia 17.5mm or 9 pcs of drop cables with diameter 2x5mm or 9 pcs of cables with diameter 3mm, 2x3.1mm or 4 pcs of cables with diameter 7mm
- ◆ Adaptor Capacity : 36 SC simplex adaptors
- ◆ Dimension : 450 x 230(mm)